

POWERSCAN™ 9600 SERIES

Handheld industrial scanners for 1D/2D barcode reading with top flexibility



ULTRA-RUGGED WITH NEW BALANCED ERGONOMICS!

The PowerScan family of bar code readers are the ultimate industrial handheld scanners designed and constructed to withstand the toughest environmental conditions. The PowerScan 9600 imagers have an ultra-rugged design, an ergonomic shape with well-balanced weight to reduce operator stress during daily activities.

MOBILITY ENHANCES PRODUCTIVITY

The PowerScan PM9600 cordless model further enhances the operator efficiency and safety with Datalogic's STAR Cordless System™. Bidirectional radio communication and display allow users to receive immediate feedback avoiding any risk of mistakes.

The PowerScan PBT9600 cordless model is enriched with Bluetooth® 5.0 that can be paired to any device supporting Bluetooth connections, or to the Bluetooth base station.

The BC9600 base/charger has a modular design and is available with multiple interface plug-ins for standard and industrial communication, such as RS-232, USB, Standard Ethernet and Industrial Ethernet protocols.

WIRELESS CHARGING

The PowerScan 9600 scanner features Datalogic's Wireless Charging System. Based on inductive-charging technology, Datalogic's Wireless Charging System eliminates battery contacts and pins that often get dirty, bent, or broken over time – and this removes a key point of failure for devices used in industrial and retail functions.

THREE OPTIC OPTIONS TO FULFILL ANY CUSTOMER NEED

The PowerScan 9600 area imagers are available in three different optics, to satisfy any customer need. The Standard Range optic is ideal for most of the applications requiring barcode reading at intuitive distance; the High Performance optic adds the capability to decode high density barcodes together with an increased depth of field on standard 1D/2D codes; the Document Capture model is thought for Wide Angle code reading and Document Capture applications.

FEATURES

- Snappy omnidirectional reading on 1D, stacked and 2D codes, postal codes
- Standard Range and High Performance models
- Water and Particulate Sealing Rating: IP65 and IP67; Cradle IP65; 10 million hits trigger
- Center of gravity design
- Modular cradle design allowing interface expansion
- White light illumination
- High visibility OLED Display with 4-Keys /16-Keys keypad options
- Standard Range, High Performance and Document capture optics
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Datalogic's Motionix™ motion-sensing technology
- Wireless Charging reducing total cost of ownership
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI.

INDUSTRIES - APPLICATIONS

- **Manufacturing Shop Floor:**
 - Work-in-Progress
 - Sub-Assembly
 - Component Tracking
 - Quality Control
 - Time and Cost Analysis
 - Machine Replenishment /Configuration
 - Line Inventory Control
- **Warehouse and Logistic Centers:**
 - Shipping / Receiving
 - Parcel Preparation
 - Picking / Put Away
 - Automatic Sorting Back-Up
 - End of Line Sorting



POWERSCAN 9600 SERIES

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS

PowerScan PM9600

Datalogic STAR Cordless System
Radio Frequency: 433 MHz; 910 MHz;
Effective Radiated Power: 433 MHz: < 10 mW;
910 MHz: < 50 mW; Point-to-Point/Multi-Point
Configuration; Max. Readers per Radio Receiver: 16;
Two Way Communications.
Radio Range (Open Air): 433 MHz: 150 m / 492 ft
low speed; 100 m / 328 ft high speed
910 MHz: 230 m / 754 ft low speed; frequency hopping; 180 m /
590 ft high speed

PowerScan PBT9600

Bluetooth Wireless Technology
Radio Frequency: 2.4 GHz; Profiles: SPP (Serial Port Profile) and
HID (Human Interface Device); Protocol: Bluetooth 5.0 Certified.
Class 1, Class 2 and Class 3; Radio Range (Open Air): 100.0 m /
328.0 ft; Range distances are measured using the base station.
Range with connection to other Bluetooth peripherals.
Security: Data Encryption; Scanner Authentication

DECODING CAPABILITY

1D / Linear Codes

Auto discriminates all standard 1D codes including GS1
DataBar™ linear codes.

2D Codes

Aztec Code; China Han Xin Code; Data Matrix; MaxiCode;
Micro QR Code; QR Code; Dot Code

Postal Codes

Australian Post; British Post; China Post; IMB; Japanese
Post; KIX Post; Planet Code; Postnet; Royal Mail Code
(RM4SCC)

Stacked Codes

EAN/JAN Composites; GS1 DataBar Composites; GS1
DataBar Expanded Stacked; GS1 DataBar Stacked; GS1
DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417;
PDF417; UPC A/E Composites

Digital Watermarking

Digimarc Barcodes (HP and DC models)

ELECTRICAL

Current

Corded models: Operating (Typical):
SR: 200mA @ 5V; 120mA @ 12V. HP/DC: 280mA @ 5V / 140mA
@ 12V. Standby/Idle (Typical): 187mA @ 5V / 92mA @ 12V.
Cordless models: Operating 480 mA @ 3.7 V. Charging
(Typical) < 15 W.
Cradle BC96xx only: 150 mA @ 5 V (Operative)

Input Voltage

Corded models: 5 - 30 VDC ± 5%
Cordless models: Host powered: 5V DC ± 5% or 10 - 30 VDC
External power supply: 10 - 30 VDC ± 5%

Battery

Battery Type: Lithium-Ion: 3350 mAh
Charge time @ 12 VDC: 2.5 hours to charge up to 95%,
3.2 hours to charge 100%, External Power.
Reads per charge: 80,000

ENVIRONMENTAL

Ambient Light

0 - 100,000 lux

Drop Resistance

Withstands 50 drops from 2.5 m / 8.2 ft @ 20 °C / 68 °F;
Withstands 50 drops from 2.0 m / 6.6 ft @ -20 °C / -4 °

Trigger Resistance

Withstands 10 million hits

ESD Protection (Air Discharge)

20 kV

Humidity (Non-Condensing)

0 - 95%

Particulate and Water Sealing

IP67 and IP65; Cradle IP65 (specific models)

Temperature

Operating: -20 to 50 °C / -4 to 122 °F
Storage/Transport: -40 to 70 °C / -40 to 158 °F
Charging: 0 to 40 °C / 32 to 104 °F nominal; 0 to 35 °C / 32 to
95 °F ideal

INTERFACES

Interfaces

RS-232 / USB / Ethernet and Industrial Protocols

PHYSICAL CHARACTERISTICS

Colors Available

Yellow/Black

Dimensions H x L x W

19.8 x 14.0 x 7.9 cm / 7.8 x 5.5 x 3.1 in

Display

PM9600-D/DK: 1.8" OLED graphic display;
Font Dimensions: User selectable.

Keyboard

PM9600-D: 4 Keys, PM9600-DK: 16 Keys; Configurable

Weight

PD9630: 318 g / 11.2 oz, PBT9600: 415 g / 14.6 oz,
PM9600: 425 g / 15.0 oz, PM9600-D: 445 g / 15.7 oz,
PM9600-DK: 455 g / 16.0 oz

READING PERFORMANCE

Imager Sensor

1280 x 800 pixels

Light Source

Aiming: 630 - 680 nm VLD
Illumination: White LED reading light

Print Contrast Ratio (Minimum)

15%

Reading Angle

Pitch: +/- 52°; Roll (Tilt): 360°; Skew (Yaw): +/- 52°

Field of View

SR and HP: 38° H, 24° V

Reading Indicators

Beeper (Adjustable Tone and Volume); Datalogic's 3GL™
(Three Green Lights) technology for good-read feedback;
Datalogic 'Green Spot'; Dual Good Read LEDs; Vibration.

Resolution (Maximum)

SR/DC: 1D Codes: 3 mil; 2D Codes: 6 mil
HP: 1D Codes: 2.5 mil; 2D Codes: 4 mil

READING RANGES

Typical Depth of Field

Minimum distance determined by symbol length and scan
angle. Printing resolution, contrast, and ambient light
dependent.

SR Models

Code 128
5 mils: 6.4 to 30.9 cm / 2.5 to 12.2 in
20 mils: 4 to 103.7 cm / 1.6 to 40.8 in
40 mils: 5.5 to 175 cm / 2.2 to 68.9 in
EAN/UPC 13 mils: 4 to 67.5 cm / 1.5 to 26.5 in
DataMatrix 10 mils: 6 to 30 cm / 2.5 to 11.8 in

HP Models

Code 128
2.5 mils: 6.3 to 11.5 cm / 2.5 to 4.5 in
5 mils: 3.8 to 41 cm / 1.5 to 16.1 in
40 mils: 5.5 to 242.9 cm / 2.1 to 95.6 in
EAN/UPC 13 mils: 4 to 120 cm / 1.5 to 40.2 in
PDF417 10 mils: 0.5 to 46.1 cm / 0.2 to 18.1 in
DataMatrix 10 mils: 4.2 to 32 cm / 1.6 to 12.6 in

SAFETY & REGULATORY

Agency Approvals

The product meets necessary safety and regulatory
approvals for its intended use.
The Regulatory Addendum for this product can be
referred to for a complete list of certifications.

Environmental Compliance

Complies to China RoHS; Complies to EU RoHS;
Complies to R.E.A.C.H.

Laser Classification

Caution Laser Radiation - Do not stare into beam CDRH
Class II; IEC 60825 Class 2

LED Classification

IEC 62471 LED Class: Exempt

UTILITIES

Datalogic Aladdin™

Datalogic Aladdin configuration program is available for
download at no charge.

OPOS / JavaPOS

OPOS and JavaPOS Utilities are available for download
at no charge.

WARRANTY

Warranty

3-Year Factory Warranty

ACCESSORIES

Base Stations / Chargers




BC9630 Base station/charger Multi-Interface
BC9631 Base station/charger Multi-Interface, IP65

Battery



RBP-PM96 Removable battery

Multi-Battery Charger



MC-P096-M2 Multi Battery Charger 2 slots
MC-P096-M4 Multi Battery Charger 4 slots
MC-P096-E2 Extension modules 2 slots

Holder



HLD-P096 Desk/Wall Holder (HLD-9600)