

# 3 inch thermal kiosk printing mechanism with presenter

80mm print width with presenter

# PMU2300III

Kiosk, Kiosk

### Applications

- Kiosk
- Retail
- Ticketing



## TOMORROW'S PRINTING TODAY

Citizen Systems Corporation, 1411 W. 190th Street, Suite 675, Gardena, CA 90248, USA



# CITIZEN

### Specifications

Model	PMU2300III
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	150 mm /sec.
Media Width (min to max)	80mm
Media Thickness (min to max)	60 to 87 μm
Interface	Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB
Power supply	Input voltage: DC 24V± 7%
Reliability	100 Million pulses or 100 Km, 1 million cuts
Presenter	Min ticket length: 75mm, Max ticket length: 120mm
Bezel (Snout)	Equipped with four monochromatice white LEDs
Flash (Non-Volatile Memory)	256K bytes
Size (W x D x H) and Weight	PMU2300IIISN: 113×98×182, 0,9 Kg, PMU2300IIISB: 113×98×208, 1.0 Kg, PMU2300IIIPB: 113×98×260, 1.2 Kg, PMU2300IIIPN: 113×98×234, 1.2 Kg
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

### PMU2300III

### Kiosk, Kiosk

#### **Features & Benefits**

- Paper load: Easy paper loading
- Printing Speed: Prompt print out of receipts up to 150mm per seconds
- Small footprint and compact design
- Removable head design for easy cleaning and paper-jam recovery
- Wide variety of paper-holding styles and options

