

# PS900 HIGH PERFORMANCE

## 2D desktop presentation scanner



Scanning indicator



Mount to PS900

Fix to desk

Fix to desk



The Unitech PS900 is the ideal on-counter/desktop presentation imager where a large format design and high performance is required. Besides reading all common 1D and 2D barcodes, this imager is able to read digital barcodes from mobile screens (including QR codes) without losing scanning quality or performance.

Its wide field-of-view, omnidirectional scanning capability, fantastic motion tolerance and advanced decoding software, the PS900 will facilitate users to scan all barcodes at speed on their first pass.

- The PS900 comes with desktop stand. This desktop stand allows the PS900 to become tilt-able besides a fixed vertical standing position, but it also removable if desired.
- The PS900 supports multiple interfaces such as: USB/HID, USB/SPP and OPOS\* protocol. \* Additional software driver needed.
- Besides auto-sending mode this imager also support trigger mode when required. In addition the auxiliary interface offers the option to connect an additional handheld scanner.
- The PS900 features a loud but adjustable speaker and offers convenient visual confirmation of good scans.
- The PS900 comes standard with stand, 2 meter USB cable and 3 year warranty. A competitive package and at an extremely competitive price.

## PS900 High performance

Compact design and high performance reading rate

The PS900 form factor can be integrated in most situations. The imager is specially designed with performance in mind and can be used in a wide variety of applications such as:

### POINT-OF-SALES



### CUSTOMER LOYALTY



### TICKETING



### COUPONING





# EN Version 1.0 PS900 Specifications

## Operational & Performance

Technology	2D imager, 1280x1024 pixels
CPU	32-bit ARM Microprocessor
Artificial light Immunity:	100,000 lux
Light source	2700K, LED White
Scan angle	±60° skew ±54° ptich 360° roll
Field of view	Horizontal:40° Vertical:32°
Frames/second	60
Scanning rate	95.3 inches/second
Motion tolerance	no less than 3m/s
Print contrast	20% minimum reflectance difference
Indicator	Loud speaker/Beeper (adjustable), LED (2700K), MP60
Print contrast	20% minimum reflectance difference
Decoding capability	All common 1D/2D paper barcodes and mobile barcodes

## Reading distance (DOF)\*

Depth of Field	1D: 0mm to 210mm 2D: 0mm to 100mm
----------------	--------------------------------------

4 mil Code39 (9 chars)	35 mm - 70 mm
5 mil Code39 (3 chars)	25 mm - 80 mm
10 mil Code39 (3 chars)	0 mm - 120 mm
13 mil UPC (6 chars)	0 mm - 140 mm
15 mil Code39 (1 char)	0 mm - 145 mm
20 mil Code39 (1 char)	0 mm - 210 mm
6.7mil PDF417 (20 chars)	20 mm - 95 mm
10mil QR (20 chars)	10 mm - 100 mm
20mil QR (20 chars)	10 mm - 100 mm

\* Depending on width, type and quality of barcode.

## Symbologies

1D: UPC-A, UPC-E, UPC-11, EAN-13, EAN-8, ISBN, ISSN, Code39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar, Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code 93, Code 11, MSI/Plessey, UK/Plessey, China Post, China Finance, GS1 DataBar, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

Stacked code: GS1 Composite, PDF417, MicroPDF417\*  
\* = Update specific firmware required to support it.

2D: DataMatrix, QR code, Micro QR code, Han Xin Code, Aztec Code

## Regulator approvals

CE, FCC, RoHS

## Power Source

Operation Voltage	5 DC ± 0.25 V
Power:	Working: 410 mA (Max: 700 mA) Standby: 300 mA

## Enclosure

Dimension:	145 mm × 82 mm × 153 mm (without stand) 187 mm × 112 mm × 153 mm (with stand)
Weight:	482g (without stand / without cable) 755g (with stand / without cable)
Cable	Black straight 2.0m USB cable

## Material

Case material:	PC
Exit Window Material:	Tempered glass

## Environmental

IP Rate	IP52
Operating Temperature	0°C to 50°C
Storage Temperature	-40°C to 70°C
Relative Humidity	5% to 95% non-condensing

## Operation modes

Scanning mode:	Auto-detection Mode Continue mode Host mode
Programming method:	Scanning special barcodes in sequence

## Connectivity

Interface	USB/HID (USB/SPP, OPOS*) * = Additional software driver needed.
Connector type	RJ-45 phone jack connector
Interfaces	RS-232, USB keyboard USB virtual COM, OPOS, JPOS

## Safety & EMC

EMC:	EN55032:2015, EN55024
Electrical safety:	EN60950-1
Photobiological Safety:	EN62471
RF Immunity:	IEC61000-4-3, 10 V/m

## Inside the box

PS900 imager
2m USB cable (straight, black)
Black desktop stand (for adjustable tilt position) + screw



## Warranty

3 Years scanner
1 Year USB cable

**unitech**  
because we care

Unitech Europe



Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com. Specifications are subjected to change without notice.

Specifications subject to change without notice. Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.