



1D & 2D



CMOS



IP50



1.2M
drop



Dual
Interface



FR4060 Akame
Stationary Scanners

DISCO

Features

Quick to Switch Mode.

The Scan Mode Switch at the top of the scanner allows users to swiftly toggle between the Regular and Screen modes.

Superior Motion Tolerance.

Exceptional motion tolerance (2.5m/s) and large FOV (46°) enhance user experience.

Superb Reading Performance.

Armed with Newland's fifth-generation of UIMG technology, the FM4060 is capable of reading 1D as well as high-volume 2D barcodes on the screen covered with protective film.

1.2m Drop Resistance.

The scanner withstands multiple 1.2m drops to concrete (six sides, one drop per side)

IR Trigger.

The IR sensor in the scanner enables speedy capture of barcodes presented to it, markedly increasing throughput and productivity.

Application scenarios.

POS, customer service desk, ticket validators, O2O.

Suggested industries



Retail

FR4060 Akame Technical specifications

Data Capture

1D	All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Chinese Sensible Code.
Image Sensor	CMOS 752*480
Aiming	Red LED (625±10nm)
Illumination	Red LED (625±10nm)
Depth of Field EAN 13 (13mil)	5-180mm
Field of View Horizontal	45°
Field of View Vertical	28.5°
Scan Angle Roll	360°
Scan Angle Pitch	±60°
Scan Angle Skew	±55°
Motion Tolerance	2.5m/s
Minimal Print Contrast	25%

Performance

Processor	0390 Chip+MCU
-----------	---------------

Physical

Current @ 5VDC Operating	150 mA
Current @ 5VDC Standby	120 mA
Dimensions (mm)	83(W)x81(D)x148(H)mm
Input Voltage	5VDC±5%
Interfaces	RS-232, USB, PS/2 (Hardware version 2.1 required)
Material	PC, ABS
Notifications	Beep, LED indicator
Power Supply Input	DC5V, 1.5A
Power Supply Output	AC100~240V, 50~60Hz
Weight	292g

Environmental

Operating Temperature	-20°C to 50°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±14 kV (air discharge), ±8 kV (direct discharge)
Drop	1.2m
IP Rating	IP50

Accessories

Standard	USB Cable
----------	-----------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

FR4060 Akame Technical specifications

Optional	RS232 Cable, Adapter, PS/2 Cable
----------	----------------------------------

Certifications

Hardware	FCC Part15 Class B, CE EMC Class B
----------	------------------------------------

Warranty

Standard	5 years
----------	---------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved