



**HR42 Halibut  
HD Bluetooth**  
Handheld Scanners

## Features

### Strong Wireless Connectivity.

The HR42 HD Halibut Bluetooth comes equipped with Bluetooth 5.0, giving you the freedom to scan barcodes up to 50 meters away from the cradle. Energy efficiency, quick data rate and easy pairing are just a few of the perks of this Bluetooth connection.

### Extensive Capabilities.

In addition to excelling at scanning high density barcodes, the HR42 HD Halibut Bluetooth extends its data capture capabilities by also providing the added value of postal barcode decoding.

### Superior Megapixel Performance.

Thanks to its 1280x960 pixel CMOS sensor, the HR42 HD Halibut Bluetooth easily captures high resolution images

and brings the scanning performance to a whole new level.

### Exceptional Aiming & Illumination.

Designed with the user in mind, the HR42 HD Halibut Bluetooth utilizes a highly visible laser aimer in order to achieve an accurate target. Along with the laser aiming capabilities, there is a flicker-free, soft white illumination to reduce fatigue during demanding activities.

### IR Sensor.

Even when barcodes are presented 40cm away from the HR42 HD Halibut Bluetooth, the IR sensor is activated.

### Rugged Industrial Construction.

Built for tough environments, the HR42 HD Halibut Bluetooth is built into an IP42 sealed and drop resistant (1.8M) housing.



## Suggested industries



# HR42 Halibut HD Bluetooth Technical specifications

## Data Capture

1D	All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Aztec, Maxicode.
Image Sensor	1280×960 CMOS
Aiming	650nm laser diode
Illumination	White LED
Scan Modes	Automatic Batch, Manual Batch
Depth of Field EAN 13 (13mil)	25-155mm
Depth of Field Code 39 (5mil)	50-100mm
Depth of Field PDF417 (6.67mil)	40-105mm
Depth of Field DataMatrix (10mil)	40-110mm
Depth of Field QR (15mil)	35-155mm
Field of View Horizontal	40.5°
Field of View Vertical	30.4°
Scan Angle Roll	360°
Scan Angle Pitch	±50°
Scan Angle Skew	±50°
Motion Tolerance	2m/s
Minimal Print Contrast	25%

## Performance

Memory Flash	900KB
--------------	-------

## Physical

Battery Type	3200mAh lithium-ion battery
Dimensions (mm)	Scanner: 115.0(L)x74.0(W)x161.0(H)mm Cradle: 195.0(L)x82.5(W)x47.2(H)mm
Expected Battery Life	≥ 14 hours of continuous operation, up to 30,000 scans per charge
Expected Charge Time	4 hours
Interfaces	RS-232, USB
Notifications	Beep, LED indicator
Power Consumption	2160mW (typical)
Weight	Scanner: 230g Cradle: 146g

## Wireless

Radio Technology	2.4 to 2.2835 GHz ISM Band, Bluetooth 5.0, BLE
Wireless Distance (max.)	30m (in open space)
Communication Modes	Automatic Batch & Manual Batch modes

## Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
-----------------------	-------------------------------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

# HR42 Halibut HD Bluetooth Technical specifications

Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5%~95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (direct discharge); ±16 KV (air discharge)
Drop	1.8m
IP Rating	IP42

## Software

Configuration Tools	Nset
---------------------	------

## Certifications

Hardware	FCC Part 15 Class B, CE EMC Class B
----------	-------------------------------------

## Warranty

Standard	3 years
----------	---------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved