MP6000 SCANNER/SCALE



Multi-Plane 1D/2D Bioptic Imager

ZEBRA

REDEFINE THROUGHPUT AND THE CUSTOMER EXPERIENCE IN THE BUSIEST POS LANES WITH HIGH PERFORMANCE 1D/2D BAR CODE CAPTURE.

Everyone knows first impressions are important. But in retail, last impressions can count even more. POS lanes are your last touchpoint with your customer — a touchpoint that can make or break a sale and the customer experience. Keeping checkout lines moving couldn't be more important — or more challenging. Manufacturers are using new GS1 DataBar and 2D bar codes to improve inventory management throughout the retail supply chain. Customers are rapidly adopting electronic bar codes that represent loyalty cards, discount coupons and gift cards for their value and convenience, since they can be stored on the one device they have with them at all times — their mobile phones. If your POS can't accommodate these codes, cashiers have to manually enter the bar code data, resulting in long wait times at the POS, and frustrated, dissatisfied customers. But with the MP6000 multi-plane imager, your POS is ready for any 1D and 2D bar code, whether it is printed on paper, a plastic loyalty card or displayed on the screen of a mobile phone. Plus, a modular design allows you to add new capabilities when new business needs arise. The result? No more long wait times at the POS. Reduced risk of abandoned sales. An investment that will serve your needs today and well into the future. And a great last impression that will foster increased loyalty and return visits.



Unsurpassed scanning performance

Scans bar codes at a higher rate than any laser bioptic scanner available today with Zebra's industry leading, proven imaging technology

Capture any bar code

Auto-discriminate reading of 1D and 2D bar codes: on paper labels — even if they are damaged, on plastic loyalty or gift cards or on the screen of a mobile phone

Exceptional reliability, cost-savings and total cost of ownership (TCO)

Minimize breakdown and maintenance costs — there are no moving parts in the scan engine, reducing power consumption by at least 30 percent; its capacitive buttons won't wear out

Customisable to meet the needs of your store and your customers

With six ports, you can easily add new capabilities, such as a scale, a Customer Side Scanner to allow customers to scan bar codes on their mobile phones and their loyalty cards, handheld scanners and EAS

Unprecedented management capability

Complimentary management software enables remote management of the entire scanner solution — scanner, scale and all attached peripherals

Sapphire glass

The horizontal scan window's best-in-class glass is virtually impervious to scratches and wear and tear

Integrated EAS support

Supports the Checkpoint® or Sensormatic® system you have in place today — no need to spend time and money to upgrade

Whisper quiet

Unlike laser scanners, there is no motor noise, so the MP6000 is practically silent, improving the POS environment

Easy to use

Omni-directional scanning plus a 6-sided 720° coverage zone — just swipe and go

Optional customer side scanner

Allow customers to simultaneously scan their own loyalty cards, coupons, impulse buy items and bar codes displayed on their mobile phones — can be added at any time

Easy deployment

Fits into existing checkstands

Three programmable buttons

Brings push button simplicity to a wide variety of POS processes to further improve throughput

GET YOUR POS LANES READY FOR THE CUSTOMERS OF TODAY AND TOMORROW WITH THE MP6000

FOR MORE INFORMATION, VISIT WWW.ZEBRA.COM/MP6000 OR ACCESS OUR CONTACT DIRECTORY AT WWW.ZEBRA.COM/CONTACT

MP6000 Specifications

scanner and scanner/scale: . L x 11.5 in. W x 4.00 in. D x 5.00 in. H nm L x 292 mm W x 102 mm D x 128 mm H um scanner and scanner/scale: n. L x 11.5 in. W x 4.00 in. D x 5.00 in. H nm L x 292 mm W x 102 mm D x 128 mm H th x 292 mm W x 102 mm D x 128 mm H t scanner: n. L x 11.5 in. W x 4.00 in. D x 5.00 in. H nm L x 292 mm W x 102 mm D x 128 mm H scanner: 15.2 lb./6.9 kg scanner/scale: 18.3 lb./8.3 kg um scanner/scale: 18.3 lb./8.3 kg um scanner/scale: 16.2 lb./7.4 kg t scanner: 12.0 lb/5.4 kg lb. in 0.01 lb. increments/15 kg in 5 g increments kimum static weight: 300 lb./136 kg le can be added after scanner installation (most countries) gle-cable and dual-cable protocols npatible with Mettler and Bizerba price computational scales ins: lb. in 0.005 lb. increments and 6-15 kg in 5 g increments kg in 2 g increments and 6-15 kg in 5 g increments le-head and dual head remote scale displays il heads rotate throug 290° for widest viewing angles on the
scanner/scale: 18.3 lb./8.3 kg um scanner: 13.0 lb./5.9 kg um scanner: 12.0 lb./5.9 kg tscanner: 12.0 lb./5.4 kg b. in 0.01 lb. increments/15 kg in 5 g increments kgimum static weight: 300 lb./136 kg le can be added after scanner installation (most countries) gle-cable and dual-cable protocols npatible with Mettler and Bizerba price computational scales ins: 2 lb. in 0.005 lb. increments and 12-30 lb. in 0.01 lb. increments kg in 2 g increments and 6-15 kg in 5 g increments gle-head and dual head remote scale displays
kimum static weight: 300 lb./l36 kg le can be added after scanner installation (most countries) gle-cable and dual-cable protocols npatible with Mettler and Bizerba price computational scales vins: 2 lb. in 0.005 lb. increments and 12-30 lb. in 0.01 lb. increments kg in 2 g increments and 6-15 kg in 5 g increments gle-head and dual head remote scale displays
et
hire; integrated Produce Lift Bar
touch capacitive pads (no buttons to break or wear out) e, centrally located two-color decode/information bar (clear for ers and self-checkout users) eper: adjustable volume and beep tones ee programmable buttons
e shared POS port for USB/RS-232/IBM RS-485 ee USB peripheral ports powered RS-232 peripheral ports eckpoint interlock port note scale display port
DC from POS interface cable (USB PowerPlus or RS-232) ra 50-14000-148R power supply: 90-264 VRMS (110-240 nal), 47-63Hz (50-60 nominal) ver consumption: less than 5.5W while scanning
notely via SMS; locally via laptop/USB; via USB drive (self-con- ng)
kpoint included in all configurations: sckpoint interlock via optional cable ormatic support: Sensormatic ZBAMB5410 provides superior EAS deactiva- performance across both horizontal and vertical planes. The IB5410 is compatible with Sensormatic's integrated bi-optic tivators (ZBSMPROE, ZBAMB9010 and ZBAMB9010-IPS)
MENT
to 104° F/0° C to 40° C
to 104° F/0° C to 40° C F to 158° F/-40° C to 70° C

2D Symbo- logies	Aztec; Datamatrix; MicroPDF417; MicroQR Code; PDF417; QR Code
1D Symbologies	2 of 5 (Interleaved, Discrete, IATA, Chinese); Bookland EAN; Code 128; Code 39 (standard, full ASCII); Code 93; Composite Codes; Coupon Code (UPC + EAN128); EAN128; EAN-13; EAN-8; GS1 DataBar (Omnidirectional, Truncated, Stacked); GS1 DataBar Expanded coupon; GS1 DataBar Limited; GS1 DataBar Expanded (regular, stacked); JAN 8; JAN-13; Plessey; TLC -39; Trioptic Code 39; UPC-A; UPC-E; UPC-E; 2-digit Supplementals; 5-digit Supplemental; Codabar; Pharmacode (Code 32)

PERIPHERALS AND ACCESSORIES

Customer side scanner (allows self-scanning of bar codes on mobile phones, loyalty cards and impulse buy items); pole display; scale

REGULATORY

Visit www.zebra.com/mp6000 for regulatory information

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the MP6000 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to: www.zebra.com/warranty

RECOMMENDED SERVICES

Service from the Start with Advance Exchange Support (available for scanner-only configurations)

Service from the Start with On Site System Support (available for scanner-only and scanner/scale configurations)

Ideal For These Applications:

Retail

- •Grocery stores
- •Hypermarkets
- Mass merchandisers
- •Dollar stores
- Discount chains
- •Warehouse clubs
- ·Self-checkout



Multiple CMOS Array Imager

All six (6) sides; 720° coverage

640nm, controlled by item detection system

Туре

Illumination

Sides Read/

Scan Zone