



5r MULTI-TECHNOLOGY PLATFORM *leadership by design*

SCALABLE

Multiple embedded emulations allow users to standardize on a single printer for environments with mixed printer languages

INNOVATIVE

Open standard XML based platform for non-proprietary printing, job and printer control

BEST OF BREED

Aluminum die cast industrial design, ventless cooling, and high performance processor ideal for rugged environments

BUILT FOR CHANGE

Snap-in print heads allow operators to replace print heads and change resolution without service calls

SMART READY

Field upgradeability supports future RFID requirements

RFID
(((SMART)))™

THERMAL PRINTING TODAY WITH TECHNOLOGY FOR TOMORROW

Based on the 5r Multi-Technology Platform, the ThermaLine™ T5000r family is an industrial thermal bar code printer designed to operate in challenging environments. Through **leadership by design**, the T5000r combines reliability, utility, power and flexibility for demanding environments and provides the open migration to RFID for future requirements. The T5000r supports the widest range of connectivity and control without sacrificing performance and provides the ability to meet new application and compliance requirements.

The T5000r integrates real world experience that readily adapts to emerging standards. The T5000r firmware can be upgraded to keep pace with new thermal bar code printing innovations and applications.

KEY FEATURES

- 32-bit processor for ultra-fast processing and throughput performance
- 32MB SDRAM memory and 8MB Flash with font and image storage capability
- 625m ribbon reduces downtime and supply cost
- Smart Ready design provides the migration path for future RFID implementation
- Embedded Zebra, TEC, Intermec, Sato and Datamax programming language support
- Field-upgradeable XML forms printing with embedded industry standard forms and templates
- Unicode with TrueType font support for worldwide compliance and local printing requirements
- Printronix Extensible Markup Language (PXML) interface enables real-time printer management and job control

GUARANTEED BAR CODE QUALITY

The T5000r delivers dependable and reliable bar code printing for compliance labeling and accommodates higher density bar codes, increased graphics or smaller text with snap-in print heads. When used in conjunction with ODV™ technology (Online Data Validation), the T5000r provides verification of scannable bar codes at the point of label creation. Designed as RFID Smart Ready, the T5000r converts to an UHF RFID printer encoder as RFID requirements enter the supply chain. Combining bar code compliance and RFID technology the T5000r links bar code and EPC data together for storage, retrieval, electronic audits and data synchronization.

PRINTRONIX
GLOBAL PRINTING...ENABLED.

T5000^r THERMAL PRINTERS

T5000r Thermal transfer or direct transfer
Industrial grade
RFID field upgradeable

FIELD UPGRADE KIT

Upgrade the T5000r to RFID with the following upgrade kit

SLMP2 Kit Multi-protocol UHF encoder set to global frequency standards
(Excludes 8" printers (T5208r/ T5308r) Supports EPCglobal Class 0, 0+, 1, Gen 2 and Philips UCode 1.19 standards

MEMORY

DRAM 32MB standard
Flash 8MB standard (16MB optional)

PRINTING CHARACTERISTICS

Print Speed T5204r-4": 10 IPS @ 203 dpi (254mm/sec)
T5304r-4": 8 IPS @ 300 dpi (203mm/sec)
T5206r-6": 10 IPS @ 203 dpi (254mm/sec)
T5306r-6": 8 IPS @ 300 dpi (203mm/sec)
T5208r-8": 8 IPS @ 203 dpi (203mm/sec)
T5308r-8": 6 IPS @ 300 dpi (152mm/sec)

Printing Methods Thermal transfer or direct thermal
Resolution 203/300 dpi (operator interchangeable)
Printable Width 4.1" max (104mm) (T5204r/T5304r)
6.6" max (168mm) (T5206r/T5306r)
8.5" max (216mm) (T5208r/T5308r)

RFID ENCODING (OPTIONAL UPGRADE KIT) (Excludes 8" printers (T5208r/ T5308r)
UHF encoder set to global frequency standards; supports EPCglobal Class 0, 0+, 1, Gen 2 and Philips UCode 1.19 standards

Operation Modes Write/Verify/Print – writes RFID data to tag and verifies contents are written correctly, while also printing the desired image
Error Handling Modes Overstrike – when a bad RFID tag is detected, overstrikes label and applies the data to the next label
Stop – when a bad tag is detected, stops the printer to allow for user intervention
Statistics Tracking Tracks number of tags written to and number of bad tags detected

MEDIA COMPATIBILITY

Media Types Roll or fanfold
Labels, tags and tickets
Paper, film or synthetic stock
Thermal Transfer or Direct Thermal
Media Width 1.0" to 4.5" (T5204r/T5304r)
2.0" to 6.8" (T5206r/T5306r)
3.0" to 8.75" (T5208r/T5308r)
Media Thickness 0.0025" to 0.010"
Roll Core Diameter 3.0" (7.6 cm)
Maximum Roll Diameter 8.0" (20.9 cm)
Thermal Transfer Ribbon
-Ribbon Width (min/max) 1.0" to 4.33" (T5204r/T5304r)
2.0" to 6.8" (T5206r/T5306r)
3.0" to 8.75" (T5208r/T5308r)
-Maximum Ribbon Length 625m

MEDIA HANDLING CHARACTERISTICS

Tear-Off Individual label tear-off
Tear-Off Strip Label strips tear-off
Continuous Labels print continuously
Cut Label cut to length
Peel-Off Label peel and present
(peel-off mode requires rewind option)

MEDIA HANDLING OPTIONS

Rewinder Required for peel and present, not recommended for batch rewind of RFID labels
Cutter Kit Cuts labels after printing specified number of labels

OPERATOR CONTROLS & INDICATORS

Operator Controls Off Line-On Line, Test Print, Job Select, Form Feed Menu, Cancel, Enter
Message Display 32 character
Indicators Off Line-On Line, Menu

BAR CODE VALIDATION

Optional Online Data Validation (ODV) - verifies bar code quality, overstrikes failed bar codes, and reprints a label.

PROGRAMMING LANGUAGES

Standard Printronix Graphics Language (PGL)
Zebra Graphics Language (ZGL)*
TEC Graphics Language (TGL)*
Intermec Graphics Language (IGL)*
Sato Graphics Language (STGL)*
Datamax Graphics Language (DGL)*

*Printer Protocol Interpreters for ZPL, TEC, IPL, Sato and DPL with RFID commands for ZPL and Sato only

Optional XML – Extensible Mark-up Language
IPDS over Ethernet, Twinax or Coax

PROTOCOLS

Optional Telnet TN5250/TN3270

BAR CODE SYMBOLOGIES AVAILABLE

AUSTPORT, Aztec, BC35, BC412, CODABAR, Code 11, Code 35, Code 39, Code 93, Code 128 (A,B,C), DATAMATRIX, EAN8, EAN13, FIM, 125GERMAN, Interleaved 2/5, ITF14, Matrix, MAXICODE, MSI, PDF417, PLANET, PLESSEY, POSTNET, POSTBAR, ROYALBAR, RSS14, TELEPEN, UCC/EAN-128, UPC-A, UPC-E, UPC-E0, UPCSHIP, UPS11

SENSING METHODS

Transmissive, Reflective (Gap, Mark, Notch, Continuous Sensing Form)

INTERFACES

Standard RS232 Serial
IEEE 1284 (Centronics)
USB 2.0
Optional Ethernet (supports PrintNet Enterprise or PXML)
Wireless (802.11b)
(supports PrintNet Enterprise or PXML)
Coax/Twinax
GPIO (General Purpose Input/Output)

FONTS, GRAPHICS SUPPORT, WINDOWS DRIVERS

Fonts OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate, CG Triumvirate Bold, CG Triumvirate Bold Condensed
Character Set Unicode with TrueType font support
Graphic Support PCX, BMP and TIFF file formats
Windows Drivers Microsoft Windows NT/2000/XP

POWER REQUIREMENTS

Line Input 90-264 VAC (48-62Hz) PFC
Power Consumption 150 watts (typical)
Regulatory Compliance FCC-B, UL, CSA, ETSI EN 300 220, CE

ENVIRONMENTAL CONSIDERATIONS

Operating Temperature 5°C to 40°C
Dimensions 11.7" W x 20.5" L x 13.0" H (T5204r/T5304r)
13.4" W x 20.5" L x 13.0" H (T5206r/T5306r)
15.4" W x 20.5" L x 13.0" H (T5208r/T5308r)
Printer Weight/Shipping Weight 37lbs/46lbs (T5204r/T5304r)
40lbs/49lbs (T5206r/T5306r)
43lbs/52lbs (T5208r/T5308r)

Printronix offers a wide selection of RFID label sizes and inlay designs as well as thermal transfer ribbons. To learn more about RFID labels and supplies or to place an order, visit www.rfid.printronix.com or call 800-733-1900.



© 2005 Printronix, Inc. All rights reserved. Printronix, ThermoLine, PrintNet, PSA, LaserLine, PGL, IGP, T5000e, T5000r, SmartLine, RFID Smart, SDLK, SLP, SLPP, SLPA, ODV, ODV Data Manager, SMT, 5r, SL5000e, SL5000r, SLPA7000r and P7000 are trademarks or registered trademarks of Printronix, Inc. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks, product names, and company names or logos herein, are the property of their respective owners. Printronix, Inc. utilizes "green" packaging for optimal recycling. Product appearance and/or specifications are subject to change without notice. PTX-409 (10/05)