



Elfin I High Resolution Inkjet Printer



Parameters

Specification	142*65*98mm (H*W*D) / 5,6*2,6*3,9 inch(Anti-shock plate is not included)
Language	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	50-600DPI
Counters	Can be set in Series No, Carton No, Pallet No, etc
Printable heights (mm)	1~12,7mm
Printing speed	0-60 m/min (300 DPI) 0-30 m/min(600 DPI)
Conveyor speed	Can be set, auto-calculated or use external synchronizer
Barcode	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR
Date format	Production date, expiry date with several formats for option
User management	3 level operating authorization (operator, technician, administrator)
Database	PC software supports MS Excel, MS Access, SQL2000, SQL2005, SQL2008 etc. database formats.
Data Source	Standard RS-232 and ethernet port, easy for integration.
Screen	1) 5inch 800*480 resolution color LCD touch screen 2) Printer can work separately without PC 3) 90 degree flip-screen design
Port	1) Ethernet: support PC software communication protocol SDK. 2) USB2.0: Support U-Disk 3) DB15: For external devices like photocell, synchronizer or alarm kit.
Ink management	Identify ink type automatically and use the best printing parameters Original HP ink cartridge guaranteed Automatic measuring system for ink consumption
Installation	Standard side printing, down printing bracket and anti-shock bracket, users can install according to their needs;
Power Supply	AC 100V-240V/50-60HZ, 36W (Dedicated AC adaptor)
Certificate	CE, FCC



All-in-One Inkjet Printer

Controller, printhead integrated.



Variable Data

Support dynamic data, database printing.



Online Edit

5 inch touch screen.



Multi-Language Support

Support multiple language input.