

Chipset	Hi3516DV300
System	Linux operation system
RAM	16G EMMC
Image sensor	1/2.7" CMOS
Lens	
Camera	Binocular camera supports live detection
Effective pixel	2 Mega pixel, 1080P
Min. lux	Color 0.01Lux @F1.2 (ICR); B/W 0.001Lux @F1.2
SNR	≥50db (AGC OFF)
WDR	≥80db
Face Recognition - Height	1.2-2.2 m (unghi ajustabil)
Face Recognition - Distance	0.5-2 m
Face Recognition - View angle	Vertical ±40°
Face Recognition - Recording Time	<500 ms
Face Recognition - Function	Suportă bază de date cu 22.400 fețe și 100.000 înregistrări
Temperature - Range	30-45 °C
Temperature - Accuracy	±0.3 °C
Temperature - Distance	0.3-0.8 m
Temperature - Response time	<300 ms
Internet interface	RJ45 10M/100M Ethernet
Weigand port	Support input/output 26 and 34
Alarm output	1 channel relay output
USB port	1 USB port (poate fi conectat la ID identifier)
Power input	DC 12V / 3A
Power consumption	20W (MAX)
Working temperature	-15°C ~ +60°C
Humidity	5~90%, fără condens
Dimensions	123.5 (W) × 84 (H) × 361.3 (L) mm
Weight	2.1 kg
Column aperture	33 mm

