

#### INFORMATION



## 27" QHD IPS monitor with USB-C (65W) and ergonomic stand

Spacious, efficient, and built for modern work, the 27" ProLite XB2796QSC-B1 helps professionals stay productive in hybrid and office environments.

Its QHD resolution (2560x1440) offers 77% more screen space than Full HD, allowing you to view more data, compare documents side by side and multitask with ease. Slim bezels on all sides make it ideal for multi-monitor setups, while the ergonomic stand with height, tilt, swivel and pivot adjustments supports a healthy, comfortable posture throughout the day. The IPS panel delivers accurate colours and wide viewing angles, perfect for business use, video meetings and content previews.

One USB-C cable handles both video signal and up to 65W of power to your laptop, reducing cable clutter and simplifying setup. Flicker-free technology and a blue light reducer help minimise eye strain during extended use.

From data analysis to meetings, the XB2796QSC-B1 brings clarity, comfort and smart connectivity to your daily workflow.



## **Expand your view with QHD**

QHD 2560x1440 resolution offers up to 77% more screen space than Full HD, giving you plenty of room to multitask efficiently, view more content at once, and work with greater precision, without constantly switching between windows.



# Sleek design, seamless viewing

With edges so thin they're barely there, your screens blend together, creating a sleek, distraction-free workspace that's as comfortable as it is stylish.



## Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.



## Work faster and feel the difference with 144Hz

Scrolling through documents, switching windows or reviewing animations feels smoother than ever. The ultra-fast 144Hz refresh rate reduces blur and stutter, letting your eyes follow motion naturally. Whether you're deep in spreadsheets or reviewing video content, your workflow stays sharp, fluid and easy on the eyes.

### 01

#### DISPLAY CHARACTERISTICS

Design	4-side slim bezel
Diagonal	27", 68.5cm
Panel	IPS panel technology LED, matte finish
Native resolution	2560 x 1440 @75Hz (3.7 megapixel QHD)
Aspect ratio	16:9
Panel brightness	350 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln (sRGB: 96%; NTSC: 72%)
Horizontal Sync	30 - 120kHz
Viewable area W x H	597 x 336mm, 23.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black



#### INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.1.4) USB-C x1 (PD 65W)
USB HUB	x2 (1x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 1x Type-C (5Gbps, 5W)
HDCP	yes
Headphone connector	yes



#### **FEATURES**

Blue light reducer	yes
Flicker free	yes
Extra	i-Style colour
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick: Menu (Centre), Up/ Signal Select, Down/ Brightness/ OD/ Eco/ i-Style Colour, Left/ Volume Down, Right/ Volume Up, Power
User controls	picture adjust (brightness, contrast, Eco, ACR, OD, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temperature), OSD (OSD H. position, OSD V. position, OSD time, OSD background, OSD rotate, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB-C speed, USB charge, DDC/Ci control), Input select, audio settings (volume, mute audio), recall (recall all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

Display position adjustments

Height adjustment

Rotation (PIVOT function)

Swivel stand

Tilt angle

VESA mounting

Cable management system

height, swivel, tilt, pivot (rotation both sides)

150mm

90°

90°

150mm

150mm

90°

150mm

150mm

90°

150mm

### 05 ACCESSORIES INCLUDED

Cables power (1.8m), USB-C (1.0m)

Other quick start guide, safety guide

### 06 POWER MANAGEMENT

Power supply unit internal

**Power supply** AC 100 - 240V, 50/60Hz

Power usage 20W typical, 0.5W stand by, 0.3W off mode

### 07 SUSTAINABILITY

Regulations CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency E class (Regulation (EU) 2017/1369)

REACH SVHC above 0.1%: Lead

### 08 DIMENSIONS / WEIGHT

**Product dimensions** 613.5 x 404.5 (550.5) x 224.5mm

WxHxD

Box dimensions W x 690 x 465 x 140mm

H x D

Weight (without box) 6.0kg

Weight (with box) 7.6kg

EAN code 4948570127023



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED