

B-FP3D-GS

Datasheet

- Expand the potential of your mobile workforce, with Toshiba's compact and rugged range of mobile 3 inch receipt printers.
- Focusing on receipt printing including queue busting, shelf tag and others, the powerful system architecture enhances the printer's performance whilst future-proofing your investment.
- Designed for the ultimate user experience, with easy operation and the flexibility to operate in the most diverse working environments.



Ready when you are!

Market leading print speeds of up to 4 inches per second, faster processing with an advanced CPU and a rapid boot time, guarantee the B-FP3D is ready to print, labels and receipts quickly and efficiently at the touch of a button. A long-life, powerful battery offers extended operational time to keep your business moving — and minimise down-time.

Simple to use

Small & light, easy to handle, the B-FP3D has been designed with the user in-mind. Simple to operate with a full colour graphical LCD display, providing easily visible status updates. Drop in, large capacity media loading, for quick and efficient media changes and a double tear-off bar for operator flexibility.

Specifications

Models

B-FP3D-GS30-QM-R Interface	Bluetooth
B-FP3D-GS40-QM-R Interface	WLAN (2.4 GHz)

General

Print Method	Direct thermal
Printhead	Flat head
Dimensions (W x D x H)	116 x 150 x 80 mm
Weight	650 g (with battery)
Memory	64 MB (FROM), 32 MB (SRAM)
Durability	1.6 m (multiple drops to concrete)
User interface	128 x 128 pixel graphic colour display 2 x LED (colours: green, amber, red), 3 x key
Operating Temperature / Humidity	-15°C - 50°C (5°F - 122°F), 25 - 85% non-condensing relative humidity (RH)
Storage Temperature / Humidity	0°C - 40°C (32°F - 104°F), 25 - 85% non-condensing relative humidity (RH)
Battery	Lithium ion battery 7.4V, 2500 mAh

Print

Resolution	203 dpi (8 dots/mm)
Sensor	Reflective, transmissive
Max. Speed	152 mm/second (6 ips)
Max. Print Width	72 mm
Max. Print Length	Batch: 5-995 mm Receipts with black mark: 5-995 mm
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, POSTNET, RM4SCC, KIX-Code, GS1 Databar, Plessey
2D Codes	Data Matrix, PDF417, QR Code, Maxi Code, Micro PDF417, Micro QR, GS1 Data Matrix
Fonts	Bitmap font, outline font, price font, TTF, OTF, writable characters

¹⁾ available for GS40 model only.

Media

Alignment	Centred
Backing Paper Width	Label: 26-80 mm
Inner Media Core Diameter	12 mm
Outer Media Roll Diameter	68 mm
Media Type	Label, receipt, tag
Issue Mode	Batch

Software & Connectivity

Emulation	ZPL II, CPCL
Printer Driver	Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016, Windows Server 2012 R2/Server 2012, Windows Server 2008 R2, SAP, OPOS, JPOS
SDK	iOS, Android, Windows CE
Interface	USB 2.0 HS, Bluetooth V2.1 EDR, WLAN 802.11 b/g/n
Language Mode	TPCL, LABEL, RECEIPT, ESC/POS, Basic Command Interpreter (BCI)
Label Software	BarTender UltraLite (co-packed)
IoT Device Management	SOTI Connect ¹⁾

Options

Common	Spare battery, shoulder strap, 1 & 6 slot battery chargers, 1 & 4 slot cradle chargers, carry case, AC & DC adapters, vehicle cigarette lighter 12V adapter
--------	---



Toshiba Tec Germany Imaging Systems GmbH

Carl-Schurz-Str. 7
41460 Neuss, Germany

Telephone
+49 2131-1245-0

Website
www.toshibatec.eu



B-FP3D-GH

Datasheet

- Expand the potential of your mobile workforce, with Toshiba's compact and rugged range of mobile 3 inch label printers.
- Focusing on label printing including price mark-down, shelf labelling, shipping labelling and others, the powerful system architecture enhances the printer's performance whilst future-proofing your investment.
- Designed for the ultimate user experience, with easy operation and the flexibility to operate in the most diverse working environments.



Ready when you are!

Market leading print speeds of up to 6 inches per second, faster processing with an advanced CPU and a rapid boot time, guarantee the B-FP3D is ready to print, labels and receipts quickly and efficiently at the touch of a button. A long-life, powerful battery offers extended operational time to keep your business moving — and minimise down-time.

Simple to use

Small & light, easy to handle, the B-FP3D has been designed with the user in-mind. Simple to operate with a full colour graphical LCD display, providing easily visible status updates. Drop in, large capacity media loading, for quick and efficient media changes and a double tear-off bar for operator flexibility.

Specifications

Models

B-FP3D-GH30-QM-R Interface	Bluetooth
B-FP3D-GH40-QM-R Interface	WLAN (2.4 GHz)
B-FP3D-GH52-QM-R Interface	Bluetooth + WLAN (dual band for 2.4 GHz/5 GHz)

General

Print Method	Direct thermal
Printhead	Flat head
Dimensions (W x D x H)	116 x 150 x 80 mm
Weight	660 g (with battery)
Memory	64 MB (FROM), 32 MB (SRAM)
Durability	1.6 m (multiple drops to concrete)
IP54 compliant	yes, excluding the paper path
User interface	128 x 128 pixel graphic colour display 2 x LED (colours: green, amber, red), 3 x key
Operating Temperature / Humidity	-15°C - 50°C (5°F - 122°F), 25 - 85% non-condensing relative humidity (RH)
Storage Temperature / Humidity	0°C - 40°C (32°F - 104°F), 25 - 85% non-condensing relative humidity (RH)
Battery	Lithium ion battery 7.4V, 2500 mAh

Print

Resolution	203 dpi (8 dots/mm)
Sensor	Reflective, transmissive
Max. Speed	152 mm/second (6 ips)
Max. Print Width	72 mm
Max. Print Length	Batch: 5-995 mm Receipts with black mark: 5-995 mm Peel-off: 8-58 mm
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, POSTNET, RM4SCC, KIX-Code, GS1 Databar, Plessey
2D Codes	Data Matrix, PDF417, QR Code, Maxi Code, Micro PDF417, Micro QR, GS1 Data Matrix
Fonts	Bitmap font, outline font, price font, TTF, OTF, writable characters

¹⁾ available for GH40 and GH52 models only.

Media

Alignment	Centred
Backing Paper Width	Label: 26-80 mm
Inner Media Core Diameter	12 mm
Outer Media Roll Diameter	68 mm
Media Type	Label, receipt, tag
Issue Mode	Batch, peel-off

Software & Connectivity

Emulation	ZPL II, CPCL
Printer Driver	Windows 10/8.1/8/7 (32/64 bit), Windows Server 2016, Windows Server 2012 R2/Server 2012, Windows Server 2008 R2, SAP, OPOS, JPOS
SDK	iOS, Android, Windows CE
Interface	USB 2.0 HS, Bluetooth V2.1 EDR, WLAN 802.11 b/g/n, combo BLE v4.0 with WLAN 802.11 a/b/g/n (dual band for 2.4 GHz/5 GHz)
Language Mode	TPCL, LABEL, RECEIPT, ESC/POS, Basic Command Inter- preter (BCI)
Label Software	BarTender UltraLite (co-packed)
IoT Device Management	SOTI Connect ¹⁾

Options

Common	Spare battery, shoulder strap, 1 & 6 slot battery chargers, 1 & 4 slot cradle chargers, carry case, AC & DC adapters, vehicle cigarette lighter 12V adapter
---------------	---



Toshiba Tec Germany Imaging Systems GmbH

Carl-Schurz-Str. 7
41460 Neuss, Germany

Telephone
+49 2131-1245-0

Website
www.toshibatec.eu

