

LANDI

C20 SE

Android Desktop POS Terminal



Dependable Android performance for essential business growth.

The C20 SE is a perfect combination of stability, lightweight construction, durability, and aesthetics, designed to deliver a seamless customer experience right at the point of interaction.

www.landiglobal.com

- The durable aluminum alloy design with a triangular base offers stability and balance
- Engage consumers with a large multimedia touchscreen and user-friendly interface
- Intuitive cable management for a clean and professional look



SPECIFICATIONS

Processor	Quad-core, 2.0GHz	Weight	Single Display: 3.9kg 10.1 CFD: 4.5kg
OS	Android 13	Audio	Speaker:5W,100dB@1m, Dual Speaker MIC: Dual Microphone Headset: 3.5mm audio jack
Memory	Internal: 4GB RAM+32GB FLASH External: Micro SD Card (Up to 2TB)	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac/ax 2.4GHz and 5GHz ETH:1000M Bluetooth 5.0, support BLE
Main Display	15.6",1920x1080,FHD capacitive multi-touch	NFC (Optional)	Android NFC, EMV Contactless L1 V3.1 compliant, Supports ISO / IEC 14443 Type A / B (Only supported on the 10.1" Premium CFD)
Customer Display	Optional 1:None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3:10.1"Premium CFD (1280x800,Touch panel, QR Camera, NFC)	Camera	Optional 1: NONE Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1"Premium CFD)
Ports	1*USB Typec-C OTG 4*USB Type-A 2.0 + 1*USB Type-A 3.0 1*Micro USB (Expansion Slot) 1*RJ22 Serial port 1*RJ45 Ethernet port 1*RJ11 Cash drawer port 1*3.5mm Audio jack 1*Micro SD slot 1*Power port	Power Supply	19V / 2.37A (Single Screen) 19V / 3.42A (Dual Screen)
Buttons	1 Power key with indicator light (red&blue) 2 volumes keys 1 Function key	Environment	Operating Temperature : 0°C to +40°C Storage Temperature : -20°C to +60°C Operating Humidity: 10% to 90% non-condensing
Size	360mm (L) x 235mm (W) x 360mm (H)	Certification	CE/CB/FCC/IC/WEEE/RoHS

LAUDI

This document is not binding and the specifications above can be modified without prior consent.

