

M10 SE

Android Mobile Terminal



Pocketable Android device with front-facing NFC reader and IP65 durability.

- **Front-Facing NFC:** Equipped with front NFC for smooth, customer-facing contactless transactions—perfect for retail and transportation scenarios.
- **Business-Ready:** Streamline tasks with a 5" touchscreen, swappable battery, and support for LANDI Connect—our powerful asset management platform.
- **Durable by Design:** With IP65-rated protection and 1.2m drop resistance, the M10 SE is built for demanding conditions.
- **Fully Connected:** Stay in touch with comprehensive wireless options including 4G LTE, dual-band Wi-Fi, Bluetooth 5.0, GPS, and NFC.
- **Versatile Performance:** Equipped with a quad-core processor, dual SIM slots, and a 5MP camera for QR scanning, it's perfect for retail, logistics, field service, and more.

- Powerful processor for smooth operation (Quad-core, 2.0GHz)
- Swappable battery on duty (3000mAh/3.7V)
- Comprehensive Connectivity options (2G/3G/4G, Wi-Fi, GPS, Bluetooth 5.0)
- 5M pixels rear camera for convenient QR code reading.



| SPECIFICATIONS

Processor	A53 Quad-core, up to 2.0GHz	Positioning	AGPS, GPS, Glonass, Beidou, Galileo
OS	Android 13 Android 14 (GMS)	Camera	Front camera: 0.3M pixels fixed focus camera Rear camera: 5M pixels, autofocus and flashlight
Memory	3GB RAM + 32GB FLASH (GMS) Micro SD Card (Up to 2TB)		
Display & Touchscreen	5", 480×854 Capacitive multi-touch	NFC	Android NFC, ISO / IEC 14443 compliant, Supports Type A / B, Mifare, FeliCa, EMVCo PCD L1 Certified
Scanner	· Optional 1 : NONE · Optional 2 : LANDI Scanner module	SIM	2*SIM 1*SIM+1*eSIM (Optional)
Keypad	1* Power key (Right side) 2* scan code keys are located on each side (Optional)	Connection	1* USB-Type C 2.0 2* POGO pins
Audio	Speaker: 2W 95dB@0.1m MIC: Single-MIC Headset: USB Type-C	Battery	Main Battery: 3.7V/3000mAh, removable
Connectivity	Cellular: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4GHz and 5GHz Bluetooth: Bluetooth 5.0, support BLE	Power Supply	5V / 2A
Protection	IP65 *Certified by FCII Lab 1.2 m drop tested *Data from LANDI lab	Accessories (Optional)	· 1+1 Charging Dock · Wrist Strap · Screen Protector · Rubber Boot
Certification	CE, CB, FCC, IC, RoHS, WEEE	Environment	Operating temperature: -10 C to +50 C Storage temperature: -20 C to +55 C Operating humidity: 10% to 90% non-condensing

