

CITIZEN

The desktop printer that makes life easy

Versatile desktop printer



Fast print speed

Printing a typical courier label takes just one second with virtually instant first label printing.

Durable internal power supply

All printers feature an internal mains power supply to provide the most reliable operation and avoid the problem of external power supplies.

Thermal transfer

The CL-S6211I is thermal transfer using a wide variety of ribbons to print on all media types.

CL-S6211I

Label, Industrial Desktop

Applications

- Courier
- E-Seller
- Healthcare
- Hospitality
- Logistic / Transport
- Manufacturing
- Pharmacy
- Retail



Desktop size - industrial performance.

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Waterfront, Lotus Park, Staines-Upon-Thames, TW18 3AG, United Kingdom, +44 20 8893 1900

CITIZEN SYSTEMS EUROPE GMBH

CITIZEN

Specifications

Model	CL-S621II
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 - 4.6 inches (12.5 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, switch selectable. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons and 4 LEDs
Emulations (Languages)	Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2®, CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	231 x 289 x 270 mm, 4.5 Kg

CL-S621II

Label, Industrial Desktop

Features & Benefits

- Paper load: Durable design - Citizen's proven Hi-Lift™ all-metal mechanism
- Printing Speed: Fast print out - 6 inches per second (150 mm per second)
- Media support: Large media capacity - holds rolls up to 5 inches (127 mm)
- Ribbon options: Wide range of ribbon options - Uses up to 360 metres inside and outside wound ribbons
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Recyclable packaging
- Basic peeler

CITIZEN

CL-S621II

Label, Industrial Desktop

Model	CL-S621II
Cutter	Guillotine type, Dealer Installable
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0