

Technical Accessory Guides (TAGs)

For Associates, Resellers, ISVs and Alliance Partners

Global



Version: Active-Only

Will only show products that are known to be available for sale

Need to provide an update or change?

Contact <mailto:ns9759@zebra.com>



For Internal Use by
PartnerConnect Members Only



Sx20 Technical Accessory Guide



NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Communication Cables

Standard USB Cables

Part Number	Picture	Description	Notes	Required Items
CBL-U20755-01 or CBA-HF-UA00-071ZA		USB Cable: 7 ft. Straight, right angle connector	► RJ45 mod-jack connector on scanner side with right angle connector. ► Standard USB/A connector on host side ► 7 ft. (2.1 M) length Straight Cable ► Right angle connector on cable allows scanner to be installed in tighter/constrained locations.	
CBL-U10755-01 or CBA-HF-UA00-070ZA		USB Cable: 7 ft. Straight	► RJ45 mod-jack connector on scanner side ► Standard USB/A connector on host side ► 7 ft. (2.1 M) length Straight Cable ► Note: To prevent interference with the Sx20 stand, use only right-angle connectors. This cable is not recommended.	

RS232 Cables

Part Number	Picture	Description	Notes	Required Items
CBL-R20755-01		RS232 Cable:STD-DB9 Female, TxD on 2, 7 ft. Straight, right angle connector	► RJ45 mod-jack connector on scanner side with right angle connector. ► DB9 Female connector on host side ► 7 ft. (2.1 M) length Straight Cable ► Right angle connector on cable allows scanner to be installed in tighter/constrained locations.	Requires external power supply

Mounting Options

Part Number	Picture	Description	Notes	Required Items
STND-AD0020-04		Adjustable Stand for Sx20	► Rotates the scanner 45 degrees forward and 15 degrees backward ► Compact footprint for POS ► Slots on bottom of scanner slide into guides on stand with a click, oriented by the scanner silhouette indicator atop the stand	

BRKT-LB0020-04		"L" Bracket for Sx20	► Supports secure vertical or horizontal mounting ► Slots on bottom of scanner slide into guides on bracket with a click	
BRKT-FB0020-04		Flange Bracket for Sx20	► Used for embedding the OEM scan module in enclosures ► Slots on bottom of scanner slide into guides on bracket with a click	
3rd Party *	 1/4-20 Camera Mount	1/4"-20 Camera Mounts	► Bottom of Sx20 contains a 1/4"-20 camera mount compatible with many third-party mounting options ► Ideal for clamp, pole, swivel and wall mounting needs	

Power Supplies/Power Cords

Part Number	Picture	Description	Notes	Required Items
PWR-WUA5V4W0US		Power Supply (US)	► Used when connecting communication cables labeled above as "Requires external power supply". ► For use in US, CA, MX, JP, TW. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-253R	
PWR-WUA5V4W0IN		Power Supply (India)	► Used when connecting communication cables labeled above as "Requires external power supply". ► For use in India. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-254R	
PWR-WUA5V4W04C		Power Supply (EU, UK, Brazil, Australia, China)	► Used when connecting communication cables labeled above as "Requires external power supply". ► Includes AC adapter clips for use in EU, UK, Brazil, Australia and China. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency.	
PWR-WUA5V4W0EU		Power Supply (EU and UK)	► Used when connecting communication cables labeled above as "Requires external power supply". ► For use in EU and UK. ► 5.2V, 1.1A, 5.7W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-256R	